

Inclined plane: force along the plane and force normal to the plane

Objects of the experiment

- Measuring the force F_1 along the plane and the force F_2 normal to the plane of a body on an inclined plane as a function of the angle of inclination α .
- Comparing the measured forces F_1 and F_2 with the forces calculated through vectorial resolution of the force of gravity G .

Principles

The motion of a body on an inclined plane can be described most easily when the force exerted by the weight G (force of gravity) on the body is vectorially resolved into a force F_1 along the plane and a force F_2 normal to the plane. The force along the plane acts parallel to a plane inclined at an angle α , and the force normal to the plane acts perpendicular to the plane (see Fig. 1). For the absolute values of the forces, we can say

$$F_1 = G \cdot \sin \alpha \quad (I)$$

and

$$F_2 = G \cdot \cos \alpha \quad (II)$$

The experiment verifies this resolution. Here, the two forces F_1 and F_2 are measured for various angles of inclination α using precision dynamometers. We can vary the angle of inclination α by moving a support with the height $h = 5$ cm to various distances s between the pivot of the inclined plane and the support point (see Fig. 1). We can say

$$\sin \alpha = \frac{h}{s} \quad (III)$$

and

$$\cos \alpha = \sqrt{1 - \left(\frac{h}{s}\right)^2} \quad (IV)$$


(I) and (III) give us the force along the plane

$$F_1 = G \cdot \frac{h}{s} \quad (V)$$

and (II) and (IV) give us the force normal to the plane

$$F_2 = G \cdot \sqrt{1 - \left(\frac{h}{s}\right)^2} \quad (VI)$$

Fig. 1 Vectorial resolution of the force of gravity G into the force F_1 along the plane and the force F_2 normal to the plane on an inclined plane



Apparatus

- 1 Inclined plane with trolley and screw model 341 21
- 1 Precision dynamometer, 1.0 N 314 141

Measuring example

$h = 5 \text{ cm}$
 $G = 1.07 \text{ N}$

Table 1: Position s of ramp support and forces F_1 and F_2 on the inclined plane

$\frac{s}{\text{cm}}$	$\frac{F_1}{\text{N}}$	$\frac{F_2}{\text{N}}$
50	0.10	1.01
40	0.12	0.98
30	0.18	0.97
20	0.27	0.97
15	0.35	0.95
10	0.59	0.81

Setup and carrying out the experiment

a) Correcting the zero point of the dynamometer

- Lay out dynamometer F_1 horizontally and correct the zero point.
- Hold dynamometer F_2 vertically downward and correct the zero point.


b) Determining the force of gravity

- Suspend the trolley freely from dynamometer F_2 using the folding metal hook and determine the weight G of the trolley.

c) Determining the force along the plane and the force normal to the plane

- Set up the inclined plane and position the support (e) at $s = 50 \text{ cm}$.
- Place the trolley (b) on the inclined plane and hook it to dynamometer F_1 (c); support the dynamometer with block (d).
- Carefully arrange dynamometer F_2 (a) as nearly perpendicular as possible to the inclined plane and lift the trolley until it is just barely touching the plane surface.
- Read off and write down forces F_1 and F_2 .
- Move the ramp support (b) to the positions $s = 40, 30, 20, 15$ and 10 cm one after another; each time arrange the dynamometer perpendicular to the inclined plane and read off and write down forces F_1 and F_2 .

Fig. 2 Experiment setup for determining the force along the plane and force to the plane



Evaluation and results

Tables 2 and 3 enable a comparison of the measured forces and those calculated using (V) and (VI). Fig. 3 shows the results plotted in a graph.

For the force normal to the plane we see a systematic deviation between the measured and calculated values. This is due to the fact that the trolley is still partially supported when the force is measured.

Table. 2: Measured an calculated force F_1 along the plane

$\frac{s}{\text{cm}}$	$\frac{F_1}{\text{N}}$ measured	$\frac{F_2}{\text{N}}$ calculated
50	0.09	0.107
40	0.12	0.134
30	0.18	0.178
20	0.27	0.268
15	0.33	0.357
10	0.53	0.535

Table 3: Measured an calculated force F_2 normal to the plane

$\frac{s}{\text{cm}}$	$\frac{F_1}{\text{N}}$ measured	$\frac{F_2}{\text{N}}$ calculated
50	1.01	1.065
40	0.98	1.062
30	0.97	1.055
20	0.97	1.036
15	0.95	1.009
10	0.81	0.927

Fig. 3 Measured (solid line) and calculated (points) values for the force F_1 along the plane and the force F_2 normal to the plane

